

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

Адрес	GlasStress Ltd. Glass stress measurement equipment 21/1 Akadeemia Str. 12618 Tallinn
Телефон	00372 655 5531
Факс	00372 655 5532
Интернет	www.glasstress.com
Работники	5
Год основания	2003
Экспортный Уровень	100 %

КОНТАКТНЫЕ ЛИЦА

Contact 1.	Мистер Johan Anton CEO Phone: 00372 655 5531 Fax: 00372 655 5532
------------	---

ПРОДУКТЫ / МАШИНЫ

Initially, GlasStress Ltd supplied instruments for laboratory use. Developments now concentrates on higher volume lower cost stress analysis equipment that may also be implemented as quality control instruments at the production line. The personnel of GlasStress Ltd has 50 years of experience in measuring stress in glass articles.

At the moment, the most sellable machine is scattered light polariscopes SCALP-05. GlasStress Ltd offers also automatic transmission polariscope AP-07 and scattered light polariscopes SCALP-04.

Scattered light polariscopes are meant for through-the-thickness stress measurement. SCALP-04 is suitable for stress measurement in architectural glass panels and automotive glazing. SCALP-05 is meant for stress measurement in automotive and solar glasses, also in chemically tempered glasses. Both polariscopes are computer controlled. Handling of the polariscopes is extremely simple: just place the the device on the glass panel to be measured and press slightly the button on the left side of the device. After ten seconds the stress profile through the panel thickness is shown on the screen of the laptop.

Polariscope AP-07 is a computer controlled device designed for automatic stress measurement in solid and hollow axisymmetric glass products (drinking glasses, bottles, neck tubes of CRT bulbs, lamps, optical fibre preforms, etc.). It permits also edge stress measurement in glass plates and automotive glazing, thickness stress measurement in strips cut out from glass plates, and measurement of stress at edge corners. Photoelastic measurements are completely automatic and take from 2 to 15 seconds. After that stress distribution in any section of the test object can be displayed on the screen. Integrated photoelasticity algorithms are used for stress calculation from the measurement data. The polariscope can be used for stress measurement near the production line. Its handling does not need any knowledge about photoelasticity or stress analysis.

ИСТОРИЯ И ПРОДУКТЫ

GlasStress Ltd is a manufacturer of internal residual stress measurement equipment for glass products. GlasStress Ltd offers automatic transmission polariscopes AP for container, tableware, lighting industries and scattered light polariscopes SCALP for automotive, architectural, solar industries.

Company Profile of **GlasStress Ltd.**

A service of glasssglobal.com, an affiliate of glasssglobal group.

Адресный материал, который Вы распечатали, является авторским правом и принадлежит Компании или третьему лицу ее Маркетинговой Службы, и все права сохранены. Любой Пользователь, который получает доступ к такому материалу, может делать это только в целях личного пользования, и использование такого материала представляет исключительный риск для Пользователя. Перераспределение или другая коммерческая эксплуатация такого адресного материала запрещены. Где такой адресный материал обеспечен третьим лицом, каждый Пользователь согласен соблюдать и быть связанным с определенными условиями использования, относящимися к такому материалу новостей. Glass Global не представляет и не подтверждает точность или надежность любой информации, содержащейся на любых адресных или внешних веб-сайтах, упомянутых в этой распечатке. www.glasssglobal.com - Международный Портал для Стекольной Промышленности - OGIS GmbH